

Amazon Web Services Data Engineering Immersion Day

Prelab1. Instructor Environment Setup July 2021

Table of Contents

Limit Instruction:	2
Introduction	2
Create the Instructor Environment	3
Changing RDS Security Group	6
Access Database from SQL Client (Optional)	9
Generate and Replicate the CDC Data (Optional)	10

Limit Instruction:

This immersion day required each student to have their own account. If you are sharing single account with multiple students by creating a multiple IAM users, Account can hit following default service limit:

- VPC VPCs per Region 5
- Glue Number of crawlers per account 50
- Glue Number of concurrent jobs runs per account 50
- Glue Maximum DPUs used by a role at one time 300
- S3 Number of buckets per account 100
- Athena Number of DDL queries you can submit at the same time 20
- Athena Number of DML queries you can submit at the same time 20
- RDS Make sure you have enough disk space available in your RDS instance, if want to run DMS Change Data Capture (CDC) as generating large amount of data can exhaust RDS disk space.
- DMS Make sure you have enough disk space available in your DMS replication instance, if want to run DMS Change Data Capture (CDC) as transferring large amount of CDC data can exhaust disk space.

Introduction

Make sure you select the appropriate AWS region and stick to it for whole of the workshop

The Database Migration Services (DMS) hands-on lab provide a scenario, where participant learns to hydrate Amazon S3 data lake with a relational database. To achieve that, participants need a source endpoint and this guide helps instructors set up a PostgreSQL database with public endpoint as the source database.

In this prelab, you will complete the following tasks:

- 1. Create a Postgres RDS source database environment.
- 2. Install the source database.

Once the full data replication is finished by DMS, go to the next step if the CDC lab is required:

3. Execute Lambda function to generate CDC data at the source database environment, to demonstrate CDC (Change Data Capture) replication within DMS.

Relevant information about this prelab:

- CloudFormation execution time: 15 minutes
- Source DB installation time: 20 mins

In an instructor-led AWS event, participants can get the Postgres RDS database detail from an event dashboard. (The instructor is required to update the database information before each event)



The instructor setup is also available in our online workshop: <u>https://aws-dataengineering-day.workshop.aws/400/410-pre-lab-1.html</u>

Create the Instructor Environment

In this section, you are going to create a PostgreSQL RDS instance as data source for AWS Data Migration Service to consume, for data migration to Amazon S3 data lake.

- 1. Launch the instructor <u>CloudFormation</u> stack. (Make sure you select the correct AWS region)
- 2. Under Capabilities select the checkbox for "I acknowledge that AWS CloudFormation might create IAM resources" and select "Create stack".

Quick create stack

Template

Template URL

https://s3.amazonaws.com/aws-dataengineering-day.workshop.aws/DMSLab_instructor_CFN.yaml

Stack description DMS Lab Instructor account

Stack name

Stack name

dmslab-instructor

Stack name can include letters (A-Z and a-z), numbers (0-9), and dashes (-).

Parameters

Parameters are defined in your template and allow you to input custom values when you create or update a stack.

LatestAmild

/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2

SourceBucket

S3 bucket which contains the source object

aws-dataengineering-day.workshop.aws

SourceKey

S3 Key which contains the source object

dmslambda.zip

Capabilities

③ The following resource(s) require capabilities: [AWS::IAM::Role]	
This template contains Identity and Access Management (IAM) resources that might provide entities access to make changes to your A Check that you want to create each of these resources and that they have the minimum required permissions. Learn more 🖸	WS account.
Cancel Create change set	Create stack

It may take 15 minutes for the stack to launch.

This stack creates a new VPC, Subnets, Security groups, EC2 instance, Route table, Routes, and an RDS Postgres instance.

Warning: make sure the Postgres database is fully populated before proceed to the DMS lab. It takes additional 20 minutes to finish, after the CloudFormation setup is completed.

dmslab-instruct	or		Г	Pulses [Justes] [20	
	.01		L	Delete Update St	ack actions V Create stack V
Stack info Events	Resources Outputs	Parameters Temp	olate Change sets		
Resources (27)					C
Q Search resources					0
Logical ID	Physical ID 🛛 🗸	Туре 🗢	Status ∇	Status reason	∇
EC2SubNet	subnet- 0b46150fc43e400bc 🖸	AWS::EC2::Subnet	⊘ CREATE_COMPLET E	-	
GenerateCDCData	GenerateCDCData	AWS::Lambda::Fun ction	⊘ CREATE_COMPLET E	-	
LambdaExecutionRole	dmslab-instructor- LambdaExecutionRole- 1QS0V5OCLPR09 🛂	AWS::IAM::Role	⊘ CREATE_COMPLET E	-	
RDSSubNet	subnet- 0477e0e0071e80331 🔀	AWS::EC2::Subnet	⊘ CREATE_COMPLET E	-	
RDSSubNet2	subnet- 00dea43618c4868d8 【	AWS::EC2::Subnet	⊘ CREATE_COMPLET E	-	
dbpgdataengdmsgroup	dmslab-instructor- dbpgdataengdmsgroup- 1pbby1ntnpdgq 🛃	AWS::RDS::DBPara meterGroup	⊘ CREATE_COMPLET E	-	
dbsgdefault	dmslab-instructor- dbsgdefault- 1p5usgck1gq0a	AWS::RDS::DBSecu rityGroup	⊘ CREATE_COMPLET E	-	
dbsubnetdefaultdmsinst ructorvpc	dmslab-instructor- dbsubnetdefaultdmsinstr uctorvpc-13e6pv5p7lbvy	AWS::RDS::DBSub netGroup	⊘ CREATE_COMPLET E	-	

You can see all resources listed below:

a. Go to the **Outputs** tab of AWS CloudFormation stack and you can find the Postgres RDS database endpoint, which will be similar to information shown in below screenshot



Changing RDS Security Group

Currently your RDS source end point is not open to connect to outside world for security reason. You need to open RDS security group to accept traffic from intended range of IP address. As it is difficult to determine range of IP address of workshop environment, so to have smooth experience of running lab you can temporally allow inbound traffic from all IP address (0.0.0.0/0 CIDR range).

Warning: It is not best practice to allow ALL CIDR range in your database security group. You should never apply open to all IP CIDR range while working on actual workload. If you are in a self-paced workshop, the better secure way is to whitelist an IP address from DMS lab.

Follow below steps to open security group for students to connect with source RDS data base for DMS full data and CDC data dump:

 Go to the <u>RDS Console</u> and double click on "dmslabinstance" DB identifier as shown below:

Amazon RDS \times	RDS > Databases		
Dashboard Databases	Databases	C Group resources C Modify Actions ▼ Restore from S3 Create database	
Query Editor	Q Filter databases	<pre>< 1 ></pre>	0
Performance Insights			
Snapshots	DB identifier	▲ Role ⊽ Engine ⊽ Region & AZ ⊽ Size ⊽ Status ⊽ CPU Current activit	ty
Automated backups	• dmslabinstance	Instance PostgreSQL us-east-1c db.t2.xlarge ⊘ Available 0.75% 0.00 Com	nection
Reserved instances			_

2. Click VPC security groups under Connectivity & security tab as shown below:

RDS > Databases > dmslabinstance			Modify Actions V		
Summary					
DB identifier CP dmslabinstance CP Role Cu Instance Cu	PU 0.71% urrent activity i 0 Connections	Info Available Engine PostgreSQL	Class db.t2.xlarge Region & AZ us-east-1c		
Connectivity & security Monitoring Logs Connectivity & security	s & events Configuration Maintena	ince & backups Tags			
Endpoint & port Endpoint dmslabinstance.ccla1oozkrry.us-east-1.rds.amazonaw Port 5432	Networking Availability zone us-east-1c VPC DMSLabSourceD8 (vpc-0b8d61 Subnet group dmslab-instructor-sd-dbsubnet 1cg3wfod4konh	de6cb51adde) Put defaultdmsinstructorvpc- Cer rds	Security VPC security groups dmslab-instructor-sd-sgrdslaunchwizard2-1TQEC430639QV (sg-0fa6619e6be612a98) (active) Public accessibility Yes Certificate authority		

3. In Security group screen, Go to Inbound tab and click on Edit as shown below

C	Create Security Group Actions	*			⊥ ૨ ♦ Ø
	Q search : sg-0fa6619e6be612a98	Add filter			
ī	Name - Group ID	▲ Group Name	VPC ID VOV	wner - Description	*
	DMSLabRD sg-0fa6619e6b	e612a98 dmslab-instructor-sd-sgrdsl	a vpc-0b8d61de6cb51adde 78	9211807855 RDS Security Group	
S	ecurity Group: sg-0fa6619e6be612a Description I Inbound Outbo	a98 Dund Tags			880
£	Edit				
	Type (i)	Protocol (i)	Port Range (i)	Source (i)	Description (i)
	PostgreSQL	TCP	5432	72.21.196.67/32	
	PostgreSQL	TCP	5432	sg-0d1979886d7072628 (dmslab-instru	ucto

4. Update Inbound rule to "Anywhere" from hard coded value "**10.0.0.5/32**", as shown in below screen. Make sure to remove the "Anywhere" inbound rule from security group, as soon as you are done with DMS lab.

ype (i)	Protocol (i)	Port Range (i)	Source (i)		Description (i)	
PostgreSQL ᅌ	TCP	5432	Custom ✓ Anywhere	0.0.0.0/0, ::/0	e.g. SSH for Admin Desktop	×
PostgreSQL ᅌ	TCP	5432		sg-0d1979886d7072628	e.g. SSH for Admin Desktop	×
Add Rule						

- 5. If you are in an AWS hosted event, proceed to **step 8**.
- 6. If you are running both instructor and student labs in a single AWS account, for example in a self-paced environment, replace the "Anywhere" rule by an IP address from student lab instead. In this example, we will allow AutoComplete DMS lab to access the RDS.

Securi	ity Groups (1/1	10) Info		C Actio	ns 🔻 🛛 C	reate security group
Q Fil	ter security groups					< 1 > 💿
	Name	▼ Security group	D V	Security group name	7	VPC ID
	-	sg-0df2c1eaec	7ad9610	default		vpc-0ed25e9c4c852a
	DMSLabRDS-SG	sg-0f234a18e7	7dc1582	dmslab-instructor-sgrdslaunchw	izard2-1FNR	vpc-07233b6557617
	-	PEVLA7E	vpc-0ed25e9c4c852a			
Details Inbou	Inbound rule nd rules	es Outbound rules	Tags			Edit inbound rules
Туре	Protoco	ol Port range	Source	,		Description - optional
Postgre	SQL TCP	5432	23.21.225	.101/32		-
Postgre	SQL TCP	5432	sg-047810 Y3OVJ46A	63b68b3d05b2 (dmslab-instructor- APB2J)	sgDMSLabSG-	-

- 7. Go to <u>VPC NAT gateways Console</u>, and look for the IP address you need to add to the RDS security group.
 - If you are running DMS hands-on lab, note down the IP address tagged with "dmslab-student".

New VPC Experience		
Tell us what you think	NAT gateways (1/2) Info	s 🔻 Create NAT gateway
VPC Dashboard New		
Filter by VPC:	Q Filter NAT gateways	< 1 > ©
C Select a VPC	Name	message $ abla Elastic IP address $
VIRTUAL PRIVATE	NatGateway nat-095cf3cdd2514f3e7 OAvailable -	184.73.4.41
Your VPCs New	NatGateway nat-04b101c8c741c31a0 O Available -	23.21.225.101
Subnets	=	
Route Tables	Details Monitoring Tags	
Internet Gateways New		
Egress Only Internet Gateways _{New}	Tags	Manage tags
Carrier Gateways New		
DHCP Options Sets New		
Elastic IPs New	Key Value	
Managed Prefix Lists New	aws:cloudformation:stack-name dmslab-student	
Endpoints	aws:cloudformation:logical-id NatGateway	

• Or if you are running the AutoComplete DMS Lab, copy the IP address tagged with "auto-dmslab".

New VPC Experience Tell us what you think	NAT gotowove (1/2) int	Create NAT gateway
VPC Dashboard New		create the gateway
Filter by VPC:	Q Filter NAT gateways	< 1 > ③
Select a VPC	Name ∇ NAT gateway ID ∇ State ∇ State message ∇	Elastic IP address
VIRTUAL PRIVATE CLOUD	NatGateway nat-095cf3cdd2514f3e7 ② Available -	184.73.4.41
Your VPCs New	NatGateway nat-04b101c8c741c31a0 🔗 Available -	23.21.225.101
Subnets	=	
Route Tables	Details Monitoring Tags	
Internet Gateways New		
Egress Only Internet Gateways <mark>New</mark>	Tags	Manage tags
Carrier Gateways New	Q Search tags	
DHCP Options Sets New	- Journ augs	
Elastic IPs New	Key Value	
Managed Prefix Lists New	aws:cloudformation:stack-name auto-dmslab	
Endpoints	aws:cloudformation:logical-id NatGateway	

8. Click on **Save**. Now everyone will be able to connect to source RDS instance for lab purpose to ingest data using DMS endpoint.

Q search : sg-0fa6619e6be612a98 Ad	d filter			
Name - Group ID	▲ Group Name - V	/PC ID ··· Owner	- Description	•
DMSLabRD sg-0fa6619e6be612a9	8 dmslab-instructor-sd-sgrdsla v	pc-0b8d61de6cb51adde 789211807855	RDS Security Group	
Security Group: sg-0fa6619e6be612a98				
Description Inbound Outbound	Tags			
Edia				
Edit				
Туре (i)	Protocol (i)	Port Range (i)	Source ()	Description (i)
PostgreSQL	TCP	5432	0.0.0.0/0	
PostgreSQL	TCP	5432	::/0	
PostgreSQL	ТСР	5432	sg-0d1979886d7072628 (dmslab-instructo	0

Note: Make sure to remove "Anywhere" inbound rule from security group as soon as you are done with DMS lab.

Optionally, you can read though the documentation to better understand the source database environment. The GitHub repository for aws-database-migration-samples is located here:

https://github.com/aws-samples/aws-database-migrationsamples/tree/master/PostgreSQL/sampledb/v1

Access Database from SQL Client (Optional)

You can follow below instruction to setup SQL Workbench to access your Postgres Database from SQL client:

https://aws.amazon.com/getting-started/tutorials/create-connect-postgresql-db/

In SQL Workbench:

Run following query to find out all Schema and table created.

SELECT * FROM pg_catalog.pg_tables;

Ensure the following 2 functions exists. If anything is missing, check the solution at **Troubleshooting** section.

SELECT * FROM pg_stat_user_functions WHERE funcname in ('generateticketactivity','generatetransferactivity')

Use following query to analyze a table

select * from schemaname.tablename;

For example:

select * from dms_sample.player;

• • •						SQL	Workbench/J Ne	•••					SQL
) I 🔘 🔀	< > > 📰 🛲 💷 🗅	× 🖶 🔽 -	¥ 😼 🛙	5 CP 🖷		User=n	naster, Schema=				₹	3 😼 😢 🖦 🗍	🗊 🔚 User=m
							Stat						
1 SELECT * FROM	pg_catalog.pg_tables;							Realect #	from dmc c	ample players			
4								S Select *	Troin anis_sa	amp te . p tayer;			
							Result 1	AT					
schemaname	tablename	tableowne	r tablespac	e hasinde	xes hasrul	es hastrige	gers rowsecurity						
dms sample	player	master		true	false	true	false	id s	port_team_id	last_name	first_name	full_name	
dms_sample	seat_type	master		true	false	true	false	1	131	Adam Loewen	Adam	Loewen	
dms_sample	seat	master		true	false	true	false	11	131	A.J. Pollock	A.J.	Pollock	
dms_sample	sport_division	master		true	false	true	false	21	131	Alex Sanabia	Alex	Sanabia	
dms_sample	sport_league	master		true	false	true	false	31	131	Andrew Chafin	Andrew	Chafin	
pg_catalog	pg_statistic	rdsadmin		true	false	false	false	41	131	Andy Marte	Andy	Marte	
pg_catalog	pg_type	rdsadmin		true	false	false	false	51	131	Archie Bradley	Archie	Bradley	
pg_catalog	pg_policy	rdsadmin		true	false	false	false	61	131	Ren Francisco	Ren	Francisco	
pg_catalog	pg_authid	rdsadmin	pg_global	true	false	false	false	71	131	Braden Shinley	Braden	Shinley	
dms_sample	mlb_data	master		false	false	false	false	91	121	Braden Shipley	Bradin	Hagang	
dms_sample	name_data	master		true	false	false	false	01	131	Braulin Hageris	Braulin	nagens	
dms_sample	nfl_data	master		false	false	false	false	91	151	Brandon Drury	Brandon	Drury	
dms_sample	nfl_stadium_data	master		false	false	false	false	101	131	Brett Jackson	Brett	Jackson	
dms_sample	sport_type	master		true	false	true	false	111	131	Chris Herrmann	Chris	Herrmann	
dms_sample	person	master		true	false	true	false	121	131	Chris Owings	Chris	Owings	
dms_sample	sport_location	master		true	false	true	false	131	131	Daniel Hudson	Daniel	Hudson	
dms_sample	sport_team	master		true	false	true	false	141	131	David Peralta	David	Peralta	
dms_sample	sporting_event_ticket	master		true	false	true	false	151	131	Dominic Leone	Dominic	Leone	
dms_sample	sporting_event	master		true	false	true	false	161	131	Edwin Escobar	Edwin	Escobar	
dms_sample	ticket_purchase_hist	master		true	false	true	false	171	131	Enrique Burgos	Enrique	Burgos	
pg_catalog	pg_user_mapping	rdsadmin		true	taise	false	false	181	131	Evan Marshall	Evan	Marshall	
pg_catalog	pg_subscription	rdsadmin	pg_global	true	false	false	false	191	131	Gabby Guerrero	Gabby	Guerrero	
pg_catalog	pg_attribute	rasadmin		true	talse	false	false	201	131	Gerald Laird	Gerald	Laird	
pg_catalog	pg_proc	rasadmin		trué	raise	false	false	211	131	lake Barrett	lake	Barrett	
pg_catalog	pg_class	rasadmin		trué	false	false	false	221	131	Jake Jamb	Jako	Lamb	
pg_catalog	pg_aurdet	rusadmin		true	false	false	false	221	131	Janie Romak	Jane	Romak	
pg_catalog	pg_constraint	rusadmin		true	false	false	false	231	131	Jamie Komak	Jamie	Romak	
pg_catalog	pg_innerits	rusadmin		uue	ialse	laise	laise	241	131	Jason Bourgéõis	Jason	Bourgeois	

Following sections are optional you only need to execute, if you want to show change data capture replication with DMS.

Generate and Replicate the CDC Data (Optional)

Warning: This step is not required at your initial lab environment setup.

Once the full data replication in DMS lab is completed, you can start to generate extra transactions in source database to demonstrate DMS CDC (Change Data Capture) functionality.

Navigate to Lambda console and you will see a pre-built Lambda function named "GenerateCDCData".

AWS Lambda $\qquad imes$	Lambda > Functions		
Dashboard	Functions (1)		C Actions V Create function
Functions	Q Filter by tags and attributes or search by keyword	[] < 1 > ©	
Layers	Function name v Description	Runtime $ abla$ Code	e size $ abla$ Last modified $ abla$
	GenerateCDCData Function to generate CDC data	Node.js 12.x 208.	6 kB 19 hours ago

- Click on the function and scroll down. You will see the code for this function. Copy the below query and paste it in the placeholder (value) of this code line: var query_cmd= "<insert-SQL-query-here>"
- 2. Run this query first: select dms_sample.generateticketactivity(10);

enerateCDCData		Throttle Qualifier	🛛 🔻 🖉 Actions 🔻 cdc	Test Save
Code entry type	Runtime		Handler Info	
Edit code inline 🛛	Node.js 12.x	•	index.handler	
▲ File Edit Find View Go Tools Window Save Test	•			:: 0
<pre>v GenerateCDCDHa Q+ mode.modules</pre>	; context, cb) \gg { context, cb) \gg { er", moster123", ss.em.MDST, sportstickets", Your other interactions with RDS , res) \Rightarrow {			4:86 JavaScript Spaces: 4 🔅

This query will generate 10 ticket sales in batches of 1-6 tickets to randomly selected people for a random price (within a range.) A record of each transaction is recorded in the **ticket_purchase_hist** table.

3. Click on **Save** and then click on **Test** to run the function. You can create an empty event as shown here:

Configure test event	×
A function can have up to 10 test events. The events are persisted so you can switch to another computer or w and test your function with the same events.	eb browser
Create new test event	
Edit saved test events	
Event template	
Hello World	•
Event name	
cdcevent	
1-{	
2	
3 }	

You will see no error in lambda log

GenerateCDCData	Throttle Qualifiers ▼ Actions ▼ missingfunc ▼ Test Save
¥ ■ GenerateSDDData) ■ node_modules) nder_js	<pre>Index.js × ① Index.js × ② Index.js * Diamodelline * Comparison *</pre>

4. Once you've sold some tickets you can run the generateTransferActivity procedure. The following will transfer tickets from the owner to another person. The whole "batch" of tickets purchased is transferred 80% of the time and 20% of the time an individual ticket is transferred.

Run this query next in the lambda function:

select dms_sample.generatetransferactivity(10);

Click on **Save** and then click on **Test** to run the function.

Ge	nerateCDCData		Throttle	Qualifiers v	Actions v	missingfunc	•	Test	Save
-	File Edit Find View Go	Tools Window	Save Te	est 👻				R.	• P
Environment	 ▼ GenerateCDCData ▶ node_modules ● Index.js 	index.js const { Clier const { Clier exports.hand var query const cli const cli const cli const cli const cli a d a a a a a a a a a a a a a	<pre>x</pre>	<pre>bg'); ht, context, cb) => i ims_sample.generated cc{ master", i: "master123", rocess.env.H0ST, e: "sportstickets", i32 (); // Your other in</pre>	{ ransferbctivity(1 nteractions with	Ø);" RDS	4:56 Jav	aScript Space	rs: 4 🌣
		Execution Resi	ult × (+)						
		 Execution results 				Status: Succeeded	Max Memory Used:	70 MB Time: 42	:99.49 ms
		Response: { "statusCode": 200 "body": "{\"comma } Request ID: "ef8f710f-1ad2-4de5 Function logs: START RequestId: ef8f REPORT RequestId: ef8f	, nd\":\"SELECT\",\ -8a0c-4fcaba539df 8f710f-1ad2-4de5-8 710f-1ad2-4de5-8 f8f710f-1ad2-4de!	\"rowCount\":1,\"oid 6c" -8a0c-4fcaba539d6c V 40c-4fcaba539d6c 5-8a0c-4fcaba539d6c	L.":null,\"rows\": ersion: \$LATEST Duration: 4299.4	[{\"generatetra	」 nsferactivity∖" Duration: 4300 d	:\"\"}],\"fi ns Memory	elds\":[Size: 1

Note:

When enabling CDC functionality in DMS, only one DMS instance/task should activate "Ongoing replication" to avoid conflicts.

When replicating to multiple targets, the processing to fan out the updates should begin with the Amazon S3 bucket, that is the target of the DMS task responsible for Ongoing replication. The process should not begin with the source database, as only one CDC process should be tracking and setting the last committed transaction that was replicated.

Troubleshooting

1. Failed to run Lambda function 'GenerateCDCData'.

Gene	erateCDCData	Throttle	Qualifiers v	Actions v	test
i Thi	nis function belongs to an application. Click here to m	1anage it.			
Exe The	xecution result: failed (logs)	tion execution. L	earn more about return	ning results from y	our function.
Ę	<pre>{ "errorType": "error", "errorMessage": "function dms_sample.g "trace": ["error: function dms_sample.generate " at Parser.parseErrorMessage (/v " at Parser.handlePacket (/var/ta " at Parser.parse (/var/task/node " at Socket.<anonymous> (/var/tass " at Socket.emit (events.js:310:2 " at Socket</anonymous></pre>	enerateticket sticketactivit ar/task/node_ usk/node_modul k_modules/pg-p sk/node_module %)",	cactivity(integer) cy(integer) does n modules/pg-protoc les/pg-protocol/di protocol/dist/pars es/pg-protocol/dis) does not exi not exist", col/dist/parse ist/parser.js: ser.js:39:38)" st/index.js:8:	st", r.js:278:15)", 126:29)", , 42)",

Cause

The source database setup is interrupted. Some database objects, such as the function **generateticketactivity()** is missing.

Resolution

Go to <u>EC2 console</u>, reboot the instance **DMSLabEC2**. It will reload the DB and create any objects that were missing. Due to the <u>re-run issue</u>, the table sporting_event_ticket will be doubled in size at each reboot. You can manually drop the table by the following script before each reboot. Then wait for 20 minutes before checking the missing DB object again.

DROP TABLE dms_sample. sporting_event_ticket CASCADE

2. RDS source database is **out of storage** space.

Amazon RDS ×	hboard X RDS > Databases > dmslabinstance dmslabinstance						
Databases Query Editor	Summary						
Performance Insights Snapshots Automated backups	DB identifier dmslabinstance	CPU	Info ③ Storage-full	Class db.t2.xlarge			
Reserved instances Proxies	Role Instance	Current activity 3 Connections	Engine PostgreSQL	Region & AZ us-east-1d			

Or you may see 'No Space left on device' error from DMSLabEC2 system log



Cause

Check the knowledge center here

Resolution

Increate the RDS instance disk size, as a quick fix.

RDS > Databases > dmslabinst dmslabinstance	ance			Modify Actions V
Summary				
DB identifier dmslabinstance	CPU 0.75%	Info 🛞 Storage	e-full	Class db.t2.xlarge
Role	Current activity 3 Connections	Engine PostgreSQ	L	Region & AZ us-east-1d
Modity DB Instance: C	Imslabinstance			
DB engine version Version number of the database engine to be u	used for this instance.			
PostgreSQL 11.5-R1		▼		
DB instance class Contains the compute and memory capacity or	f the DB instance.			
db.t2.xlarge — 4 vCPU, 16 GiB RAM		•		
Multi-AZ deployment Specifies if the DB instance should have a stan Yes No	dby deployed in another availability zone.			
Storage type General Purpose (SSD)		•		
Allocated storage 40 © This instance supports multiple storage ranges	GiB between 20 and 65536 GiB. See all			
Scheduling of modifications				
When to apply modifications Apply during the next scheduled m Cerrent-meinterance-window-sam:05.9C Apply immediately The modifications in this request and an maintenance-window setting for this day	naintenance window nsun:05:50 ↓ pending modifications will be asynchronou abase instance.	sly applied as soc	on as possible, regardless of th	ie
Potential unexpected downtin If you choose to apply changes are also applied. If any of the po unexpected downtime.	ne immediately, please note that any cha anding modifications require downtime	nges in the per e, choosing this	nding modifications queu s option can cause	2
	Cancel	Back	Modify DB Insta	nce